

2 CEMENT WING INTO POSITION ON BODY

1 CEMENT BODY HALVES TOGETHER


3 SLIP ELEVATOR INTO RUDDER SLOT AND LINE UP WITH MODEL

ASSEMBLE MODEL IN SUGGESTED NUMERICAL SEQUENCE.

TO HOLD DECALS FIRMLY ONTO PLASTIC. WHEN DRY, COVER WITH THIN COAT OF VARNISH.

6 CEMENT COWLING TO BODY FRONT

7 CEMENT PROPELLER TO MODEL




9 CEMENT DISPLAY STAND PARTS TOGETHER CEMENT MODEL TO TOP OF STAND



4 CEMENT STRUTS IN POSITION

8 APPLY ALL DECALS

NOTE: PARTS THAT FIT SNUG, APPLY CEMENT FIRST TO EASE TENSION



5 CEMENT LANDING GEAR TO BODY

IF MODEL IS TO BE PAINTED USE ENAMEL ONLY. DO NOT USE LACQUER OR LACQUER BASE MATERIALS AS THESE SOFTEN THE PLASTIC. APPLY ALL DECALS AFTER MODEL IS PAINTED.



### INSTRUCTION PLANS

# MONOCOUCPE

# 110 special

FOR BEST ASSEMBLY RESULTS USE PLASTIC CEMENT